2" & 2 1/2" HORIZONTAL BLIND INSTALLATION INSTRUCTIONS

TOOLS YOU WILL NEED:

Measuring Tape Level 1/4" Magnetic Nut Driver Cordless Drill Screwdriver

a contraction of the second se



HARDWARE YOU WILL RECEIVE: Installation Brackets Mounting Screws Valance Clips Small Screws


Contents may include the following , depending upon the mounting options you have chosen:

3/8" Spacer Block

Support Bracket

Metal Extension Bracket

Valance Return Brackets & Corner Inserts Hold Down Brackets Cord Cleat



Hold the Installation Bracket in place.Set brackets to proper depth in the window sill and install the brackets. (Valance type will determine the depth of the bracket - CV or CVR). Insert the screws into the 1/4" magnetic nut driver and mount brackets to the wall. Use at least 2 of the 7 predrilled holes in the bracket.

Keeping Blind in "UP position". Insert the headrail into the bracket by sliding it in the open face of bracket. Close the flap to lock the blind securely into place.







VALANCE INSTALLATION

Locate groove on back of valance, place clip sideways in groove and turn clip to lock into correct position. Attach valance back to allow clips to slide into headrail. Once clips are in headrail, slightly pull valance downward until clips sit flush.

ATTACHING VALANCE RETURNS (IF NEEDED)

Place valance return insert into slot in back of return. Then slide insert with the attached return into adjoining slot on the back of the valance.







OPERATING YOUR NEW BLINDS

Each cord with individual tassels will tilt the slats in alternate directions.

The lift cord is used to raise and lower the blinds. Pull the cord away from the window to lift the blind and lock in position. Pull toward the center to release the blind from the locked position.

The slats must be open when raising or lowering the blind.

CARE & CLEANING YOUR BLINDS

Tilt slats almost all the way in one direction. Dust may be easily brushed off using a feather duster or soft cloth. Turn the slats in the other direction and repeat. Never immerse your blinds in water.

